



22

Tipo : Type :		G14		do: 13,5 mm	
Omologazione Homologation		PN	Coefficiente efflusso ridotto Low flow coefficient		Campo di taratura Setting range
E.D. 97/23/EC IV ^A Cat.(PED)		60	0,81; >3 bar 0,86		0,3 - 60,0 bar
GOST-R		60	0,81; >3 bar 0,86		0,3 - 60,0 bar
ATEX Ex II 2 G c		60	0,81; >3 bar 0,86		0,3 - 60,0 bar
ATEX Ex II 2 D c (1)		60	0,81; >3 bar 0,86		0,3 - 60,0 bar
ASME VIII Div.1		60	0,629		1,0 - 60,0 bar
Canadian Reg. CRN		60	0,629		1,0 - 60,0 bar
CONFIGURAZIONE - CONFIGURATION					
Materiale Material		Ottone Brass	Mista Ottone-Acciaio inox Mixed Brass-Stainles steel		Acciaio inox Stainles steel
Modelli Model	Con ghiera With ring nut	Con ghiera With ring nut	Con ghiera With ring nut		
	Senza Ghiera Without ring nut	Senza Ghiera Without ring nut	Senza Ghiera Without ring nut		
	Con leva With lever	Con leva With lever	Con leva With lever		
	/	/	Con apertura pneumatica With pneumatic opening		
	/	/	Pneumatica con sensore Pneumatic with sensor		
Sedi di Tenuta Seal System		N.B.R. (Std) -10 / + 100 °C E.P.D.M. -50 / + 150 °C VITON -20 / +200 °C SILICONE -60 / +200 °C PTFE -196 / +250 °C KALREZ -20 / +250 °C /	N.B.R. (Std) -10 / + 100 °C E.P.D.M. -50 / + 150 °C VITON -20 / +200 °C SILICONE -60 / +200 °C PTFE -196 / +250 °C KALREZ -20 / +250 °C Metal -196 / +250 °C		N.B.R. (Std) -10 / + 100 °C E.P.D.M. -50 / + 150 °C VITON -20 / +200 °C SILICONE -60 / +200 °C PTFE -196 / +250 °C KALREZ -20 / +275 °C Metal -196 / +450 °C
Connessione Entrata Inlet Connection		G.1/2" - 3/4" - 1" ISO228 R.1/2" - 3/4" - 1" EN10226 1/2" - 3/4" - 1" NPT DN20-25 PN16-40-60 3/4" - 1" 150-300 lb / /	G.1/2" - 3/4" - 1" ISO228 R.1/2" - 3/4" - 1" EN10226 1/2" - 3/4" - 1" NPT 3/4" - 1" - 1"1/2 Tri Clamp DN25 DIN405-11851 DN20-25 PN16-40-60 3/4" - 1" 150-300 lb		G.1/2" - 3/4" - 1" ISO228 R.1/2" - 3/4" - 1" EN10226 1/2" - 3/4" - 1" NPT 3/4" - 1" - 1"1/2 Tri Clamp DN 25 DIN405-11851 DN20-25 PN 16-40-60 3/4" - 1" 150-300 lb
Connessione Uscita Outlet Connection		G.1" ISO228 DN25 PN16-40-60 1" 150-300lb / / / /	G.1" ISO228 1"1/2 Tri Clamp DN25 DIN405-11851 DN25 PN16-40-60 1" 150-300 lb / /		G.1" ISO228 1"1/2 Tri Clamp DN25 DIN405-11851 DN25 PN16-40-60 1" 150-300 lb / /
A richiesta possono essere eseguiti collaudi dai più prestigiosi enti quali: INAIL (area ISPESL), TÜV, RINA, Bureau Veritas, ABS e Lloyd Register. On request tests can be made by the most prestigious societies, such as: INAIL (area ISPESL), TÜV, RINA, Bureau Veritas, ABS and Lloyd Register.					
Note: (1) No Modello Con leva / No Model With lever					